



TERRA-HAMMER TR 220



TERRA-HAMMER TR 220

Compact design with high impact force



RAM HEAD

The ram head with 2 ram cones allows steel pipe ramming from Ø 100 mm. An optional pulling eye maybe assembled.

END CAP

The body is thicker at the end front and rare part to increase the lifetime. The simple hose connection allows quick hose changing.

STEEL PIPE RAMMING APPLICATIONS

The TR 220 rams steel pipes up to \emptyset 100 – 600 mm over lengths of 60 m. Vertical or horizontal application possible.

Technical Data

Diameter	220	mm
Length	1.60	m
Total weight	315 (100 %)	kg
Main piston weight	121 kg (38 %)	kg
Warranty on the main piston	3	years
Frequency	320	1/min
Air consumption	7.0	m³/min
Pressure	6 – 7	bar
Theoretical impact energy	4'400	Nm
Real impact energy	1'100	Nm
Ramming energy	320'000	Nm/min
Ramming force	370	to

All data depending on ground conditions. Technical specifications can be changed without prior notice.

Steel pipe ramming with the TERRA steel giants!



TERRA OILER AND SPECIAL OIL

The synthetic HD oil with high viscosity and additives operates down to -25 °C (antifreeze) and ensures a long lifetime of your TERRA-Ram. The oil is biodegradable.



TENSIONING ACCESSORIES

During the launching procedure tensioning accessories ensure the tensioning of the TERRA-Ram against the steel pipe.



RAM RINGS / RAM PLATES

TERRA ram rings transfer the ramming energy of the TERRA-Ram into the steel pipe. All TERRA ram rings have an outer cone and a pipe stop to transfer 100 % of the energy.



CUSTOMER SERVICE

Satisfied clients worldwide and a great customer service are the result of our constant progress. The TERRA-HAMMER ram is a must have for every contractor!